

SHIMOGA DIVISION.

Abstract Notification dated 14th February 1939.

The attention of the public is drawn to the notification advertised in page Nos. 355-357, Part VI of the *Mysore Gazette*, dated 23rd February 1939, for "Constructing compound wall and repairs to Sri Rameswaraswamy Temple and other allied temples at Tirthahalli." The last date for receiving tenders is 12th of March 1939.

M. K. RAJAM IYENGAR,
Executive Engineer.

MISCELLANEOUS DEPARTMENTS

OFFICE OF THE INSPECTOR-GENERAL OF POLICE IN MYSORE, BANGALORE.

Notice No. T. C. 295—37-38, dated 19th November 1937.

The public are hereby informed that an Avery's Weigh-bridge to weigh motor vehicles is erected in the Office of the Inspector-General of Police in Mysore, Cenotaph Road, Bangalore City, and that motor vehicles brought for weighment will be weighed on payment of a fee of Rs. 10 for each weighment. A certificate of weighment will invariably be issued with each weighment so made.

F. A. HAMILTON,
Inspector-General of Police.

OFFICE OF THE LIVE-STOCK EXPERT IN MYSORE, BANGALORE.

Notification dated 11th February 1939.

It is hereby notified for the information of the public that 10 bull calves, 5 heifer calves (Amrith Mahal, Hallikar and foreign cross breeds) and three Amrith Mahal Bullocks will be sold by Public Auction by the Live-Stock Expert at the Hebbal Farm on the 20th March 1939 at 8-30 A.M.

The sale shall be knocked down in favour of the person who offers the highest bid, provided the Live-Stock Expert does not consider it unreasonably low. As soon as the sale is concluded, the purchaser shall pay the full amount and take delivery of the animals.

A. A. MONTEIRO, LIEUT.
Live-Stock Expert.

OFFICE OF THE MUZRAI COMMISSIONER IN MYSORE, BANGALORE.

Notification No. C. 1296—38-9, dated 28th February—1st March 1939.

The undermentioned articles will be auctioned in the premises of the New Public Offices, Bangalore City, at 2 P.M. on Monday the 27th March 1939.

The articles will be put up for auction singly or in lots as may be found convenient at the time.

The articles will be knocked down to the highest bidder who will have to pay the whole amount of the bid on the spot and remove the articles after the auction is over.

The decision on any question that may arise shall vest in the Officer-in-charge of the auction.

- (1) One Remington Typewriter.
- (2) One Foot-rest.
- (3) One broken chair.
- (4) Two Metallic Tapes.

S. ABDUL WAJID,
Muzrai Commissioner.

GOVERNMENT OF MYSORE—ELECTRICAL DEPARTMENT.

DAVANGERE-CHITALDRUG TRANSMISSION AND TELEPHONE LINES—CARTING.

Abstract Notification dated 15th February 1939.

Attention is drawn to this office notification, dated 15th February 1939, inviting tenders for the above work, published in Part VI, pages 363-364 of the *Mysore Gazette*, dated 23rd February 1939. The last date of receiving tenders is 13th March 1939 and the earnest money required is Rs. 200.

In the detailed notification against Serial No. 3 "Wooden Poles, 26' long" please read "Care of 4 Poles" instead of "Cart of 3 poles."

OFFICE OF THE CHIEF ELECTRICAL ENGINEER IN MYSORE, BANGALORE.

Notification No. G. N. 37, dated 3rd March 1939.

To

The Firms dealing in Wires and Cables.

GENTLEMEN,

Please be good enough to quote your best rate for the supply of the following, delivered f.o.r., Bangalore, stating therein the earliest time of delivery. Tenders should be sent addressed to the Chief Electrical Engineer in Mysore, Bangalore, on or before 30th April 1939, 12 noon, and the envelope should be superscribed with the words "Tender for Telephone Aerial Cable—30th April 1939."

Final acceptance of tender will rest with the Chief Electrical Engineer who shall not bind himself to accept the lowest or any tender or to assign any reason for the rejection of any tender.

Complete specification, with sample if possible, shall be given of the material offered.

Specification of the cable.

Miles 10.—Aerial Cable consisting of one pair of No. 14 B. & S. gauge copper conductors of not less than 97 per cent conductivity, insulated with one layer of pure and two layers of vulcanised India rubber, double cotton braided and suitable for 600 volts pressure. The wires after insulation and braiding shall have a weather proof finish, suitable for outdoor use and shall be twisted together, one being coloured red and the other black for identification. The cable shall be supplied in lengths of not less than 1,000 yards each. The cable shall conform to the latest B. S. S. or A.I.E.E. standards.

Notification No. G. N. 38, dated 4th March 1939.

Sealed tenders for the supply of the following electrical instruments (to be delivered f.o.r., Mysore and f.o.r., Hassan) will be received in the Office of the Chief Electrical Engineer in Mysore, Bangalore, up to 2 P.M. on Friday the 31st March 1939:—

- (1) TWO—A. C. Volt-meters, portable, in leather carrying case, double range 0-150-500 volts 25-133 cycles.
- (2) TWO—A. C. Ammeters, portable in leather carrying case, 0-10 amps. range.
- (3) ONE—D. C. Voltmeter, 0-150 volts range, portable in leather carrying case.
- (4) ONE—D. C. Ammeter, 0-100 amps. range, portable in leather carrying case.
- (5) ONE—D. C. Cell Testing Voltmeter, 0-5 volts range with testing spike, terminals and lead.

Specifications.—All the above instruments should be accurate to within $\frac{1}{2}$ per cent and should retain this quality for long periods in service. They shall be suitably protected and should retain their accuracy even when subject to such disturbing influences as external magnetic fields and variations in wave-forms.

Mechanically, they should be strong in construction, with cases of seasoned wood or moulded material, with light-weight moving elements not susceptible to damage during transportation; yet they should be small and light consistent with utility and strength. The A. C. Voltmeters and Ammeters shall be of the moving iron type, suitable for use on frequencies of from 15 to 133 cycles.

The D. C. Voltmeters and Ammeters shall be of the permanent magnet-moving coil type and shall be ideal instruments for ruggedness and portability.

The scales of the instruments about 5" long shall be hand calibrated by direct comparison with accurate reference standards with minor scales and knife-edge pointers used to eliminate parallax errors.

- (6) ONE—MEGGER Insulation Tester, 5,000-volts, in leather case.
- (7) ONE—"V" MEGGER 500-volts, in leather case.

Specifications.—The megger instruments should be of the constant pressure type and have a high range ohm-meter of the moving coil type. The instruments should be robust and handy for use—

- (8) TWO—RINGER continuity Testers consisting of a hand-operated magneto generator of the telephone type with a bell.

Complete specifications with drawings and photographs should be submitted along with the tenders. Earliest time of delivery should also be noted as the same will have equal weight in the acceptance of tenders.

The Chief Electrical Engineer reserves to himself the right to refuse the lowest or any tender, whole or part, without assigning any reason therefor.

Withdrawal from the quotation after it is accepted or failure to make the supply within the specified time or according to specifications will entail cancellation of the order and purchases being made at the firm's expense from other sources.

Tenders should be superscribed "Tenders for Electrical Instruments to be opened at 2 P.M. on 31st March 1939."

M. HAYATH,

For Chief Electrical Engineer.